


INDUCTIVE PROXIMITY SWITCH				
Structural category		Angular column type		
Outward appearance code		LMF1		
Appearance				
Dimension				
Flush	Detection distance		5mm	
	DC 6 ~ 36 V	NPN	NO 3005NA	
			NC 3005NB	
			NO+NC	
	~ 36 V	PNP	NO 3005PA	
			NC 3005PB	
			NO+NC	
	two wire system	NO	3005LA	
		NC	3005LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	
			NC	
			NO+NC	
Non-flush	Relay output			
	Detection distance			
	DC 6 ~ 36 V	NPN	NO	
			NC	
			NO+NC	
	~ 36 V	PNP	NO	
			NC	
			NO+NC	
	two wire system	NO		
		NC		
Control output	DC	200mA		
	SCR/Relay	300mA		
Output voltage drop DC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		50×50×1(A3 iron)		
Repeated precision		0.02		
DC/AC Response frequency		400Hz/25Hz		
Working environment temperature		-25°C ~ 75°C		
Insulation resistance		50MΩ		
Shell material		ABS Resin		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		SN04-N		